



# RAVENOL ATF T-IV Fluid

**Kategorie:** Gear oil for automatic transmissions

**Artikelnummer:** 1212102

**Oil type:** Synthetic



**Recommendation:** Aisin Warner Automatic Gearbox, BMW 83220402413 für MINI 6-Speed Aisin F21 (nur US, BMW 83227542290 für MINI 6-Speed Aisin F21, ESSO JWS3317, Fiat 9.55550-AV1, Ford 1327936, Ford WSS-M2C924-A, Ford XT-8QAW, GM 9986195, Land Rover LR002748 6-Speed Aisin F21, Land Rover LR022460, Matic K, Mazda K020-W0-049, Nissan 999MP-MTK00P für RE5F22A, Opel/GM 1940771, Opel/GM 1940774, Renault 7711172225 für Getriebe SU0 und SU1, Renault 7711218368 SU1 Gear, Suzuki 99000-22800-001, Toyota 00279-000T4, Toyota 08886-01705, Toyota 08886-81016, Toyota JWS 3309, VOLVO 1161540, VW/Audi G 055 025 A2

**Application:** Passenger car

**RAVENOL ATF T-IV Fluid** is a synthetic ATF (Automatic Transmission Fluid), designed on the basis of high quality hydrocrack oils with a special additive and inhibition, which ensure a perfect function of the automatic transmission.

**RAVENOL ATF T-IV Fluid** is universal ATF (Automatic Transmission Fluid) for automatic transmission of Toyota und Aisin AW.

**RAVENOL ATF T-IV Fluid** guarantees maximum wear protection in all operating conditions.

## Application Note

**RAVENOL ATF T-IV Fluid** was developed for use in automatic transmission, especially for Toyota and Aisin AW.

**RAVENOL ATF T-IV Fluid** can replace T, T-II and T-III Fluids.

It is advisable to flush with **RAVENOL ATF T-IV Fluid** before filling with **RAVENOL ATF T-IV Fluid**.

## Characteristics

- Very good lubricating properties also at low temperatures in winter
- High, stable viscosity index
- Very low pour point
- Excellent oxidation stability
- Protection against wear, corrosion and foaming
- Good concerted friction characteristic
- Neutral behavior towards sealing materials
- Neutral behavior by inhibition to non-ferrous metals

1L | 1212102-001

4L | 1212102-004

10L | 1212102-010

20L | 1212102-020

20L | 1212102-B20

60L | 1212102-060

60L | 1212102-D60

208L | 1212102-208

208L | 1212102-D28

1000L | 1212102-700

## Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m <sup>3</sup>	847,0	EN ISO 12185
Colour		rot	VISUELL
Pourpoint	°C	-48	DIN ISO 3016

All indicated data are approximate values and are subject to the commercial fluctuations.

RAVENOL special transmission fluids are special developments for special gears and cannot be selected on the basis of technical parameters (viscosity, etc.). Therefore the decision was made not to give technical data. Please note: RAVENOL special transmission fluid is exclusively to apply under the original number, as indicated in the product information. If you are unsure about the right transmission fluid, ask your workshop or dealership for advice on the transmission type and OEM original number or ask our experts, making sure to state the VIN code (vehicle identification number) of your vehicle. Misapplication of RAVENOL special transmission fluid can lead to malfunction of the transmission shifting problems, increased fuel consumption, unwanted slip behavior, etc. and cause the failure of the transmission. Ravensberger Schmierstoffvertrieb GmbH is not liable for transmission failures in case of wrong selection of RAVENOL special transmission fluid.