



AUTOMATIC TRANSMISSION FLUID ATF

ADDINOL ATF XN 7

PRODUCT DESCRIPTION

ADDINOL ATF XN 7 is a high-performance automatic transmission fluid combining selected synthetic base oils with an especially developed additive technology.

APPLICATIONS

- Especially developed with a high anti-wear performance and for a smooth functioning and an excellent wear protection of modern automatic transmissions with up to 7 speeds in a various range of passenger cars.
- Reduced viscosity to deliver fuel economy benefits depending on vehicle type, vehicle condition, and driving conditions.

SPECIFICATIONS

Meets and exceeds the international OEM performance requirements acc. to:

- Dexron VI
- JASO 1A-LV
- BMW 8072B, LT 71141
- Hyundai/Kia/Mitsubishi SP-IV
- Ford FNR 5
- Honda DW-1
- Mazda ATF FZ
- Mercedes-Benz 236.12/-.15/-.14/
- Nissan Matic-S
- PSA LT 71141
- VW G 055 162, G 055 005
- Peugeot LT 71141
- Toyota T-IV/WS

DELIVERY

Delivery preferable in drums and small cans.

CHARACTERISTICS

- High scuffing load capacity
- Optimized friction behaviour
- Very good anti-wear behaviour
- · Very good cold flow behaviour
- · Corrosion-preventing properties

ADVANTAGES AND BENEFITS

- Protection of heavily loaded gearbox components
- Smooth shifting behaviour and less shift time lag in common 7 speed automatic transmissions
- Extended life time duration of gearbox parts
- Reliable lubrication and quick reaction even at very low outdoor temperatures
- Stable corrosion protection





E-Mail: info@addinol.de, Internet: www.addinol.de





ADDINOL ATF XN 7

SPECIFICATIONS AND TYPICAL PARAMETERS

Feature	Test condition / unit		ATF XN 7	Method acc. to
Appearance			clear, free of contaminations, blue	visual
Density	at 15°C	kg/m³	842	DIN 51757
Kinematic Viscosity	at 40°C	mm²/s	25	ASTM D 7042
	at 100°C	mm²/s	5.4	
Viscosity Index			163	DIN ISO 2909
Dynamic Viscosity	at -40°C	mPa*s	< 8,000	DIN 51398
Flash Point	coc	°C min.	200	DIN EN ISO 2592
Pour Point		°C max.	-48	ASTM D 7346

ADDINOL - The Experts for High-Performance Lubricants

We at ADDINOL develop and produce more than 600 high-performance lubricants of the new generation. Among these are automotive lubricants for highest demands and pioneering developments for industrial applications. Our customers all over the world benefit from the high and stable quality of our ADDINOL high-performance lubricants, our expertise, and the individual customer advisory service of our competent experts. Our company has worldwide activities. ADDINOL high-performance lubricants are distributed by more than 90 international partners.

The data provided in this product sheet represent our current level of knowledge and experience. Due to the various specific application they, however, do not discharge the user from his own examination. The information provided herein may not be used to derive a legally binding warranty of specific properties or the suitability for a certain purpose of application. Detailed security-concerning and toxicological data as well as security instructions for each product can be taken from the corresponding Material Safety Data Sheets (MSDS). High-performance lubricants from ADDINOL are under continuous development. Therefore, ADDINOL Lube Oil GmbH keeps the right to change technical data in this product data sheet without notification. In case of doubt, please do not hesitate to contact our customers' advisory service.

Phone: +49 (0) 3461-845-201, Fax: +49 (0) 3461-845-555 E-Mail: info@addinol.de, Internet: www.addinol.de