



RAVENOL Diesel Performance Optimizer Premium

Kategorie: Additives

Artikelnummer: 1390241

Application: Passenger car, Truck



0.3L | 1390241-300

RAVENOL Diesel Performance Optimizer Premium is a premium fuel additive for all diesel engines for cleaning the diesel system, increasing operational safety and for the economic feasibility of diesel engines.

RAVENOL Diesel Performance Optimizer Premium Certified by TÜV (Technical Inspection Agency) Nord

RAVENOL Diesel Performance Optimizer Premium cleans the diesel system and the combustion chamber; this leads to a clean fuel injection system.

RAVENOL Diesel Performance Optimizer Premium enables saving fuel. The formation of "acidic" water is prevented and therefore, there is a higher level of protection against corrosion.

RAVENOL Diesel Performance Optimizer Premium increases the lubrication effect for low sulphur fuel.

RAVENOL Diesel Performance Optimizer Premium prolongs the service life of catalytic converters and lambda probes by means of optimum combustion.

Application Note

RAVENOL Diesel Performance Optimizer Premium

is added to the diesel fuel.

Area of application:

Diesel engines in passenger cars and lorries

Can be used preventively at every service

For all diesel fuels, summer and winter diesel

Suitable for modern common rail and pump nozzle systems

Can also be used in bio-diesel or mixtures of diesel fuel with bio-diesel

Application: Pour the contents of the container into the tank. Fuel volume up to 50 litres of diesel. Minimum fuel capacity according to volume of fuel reserve.

RAVENOL Diesel Performance Optimizer Premium is an easy to mix diesel additive which is certified by TÜV (Technical Inspection Agency) Nord.

Characteristics

- Certified efficacy by the TÜV Nord (Technical Inspection Agency)
- Cleans diesel system and combustion chamber
- Saves fuel
- No "acidic" water, corrosion protection
- Increases the lubrication effect for low sulphur fuel
- Improves the ignitability and reduces "rattling sounds" caused by fuel

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Colour		braun	VISUELL
Density at 20 °C	kg/m ³	842,0	EN ISO 12185
Flashpoint	°C	45	DIN ISO 3679

All indicated data are approximate values and are subject to the commercial fluctuations.