



#### 0.3L | 1390246-300

# **RAVENOL Diesel Power Performance**

Kategorie: Additives

Artikelnummer: 1390246

**RAVENOL Diesel Power Performance** is a highly effective fuel additive for all diesel engines, with and without exhaust treatment systems. Effectively removes deposits on the injection nozzles and in the combustion chamber, thus ensuring optimal cumbustion.

**RAVENOL Diesel Power Performance** improves the lubricating effect of low-sulfur fuel and offers very high corrosion protection. It optimizes engine performance and engine operation.

**RAVENOL Diesel Power Performance** extends the service life of catalysts and lambda sensors through optimal combustion.

## **Application Note**

#### **RAVENOL Diesel Power Performance**

is added to the diesel fuel before refueling.

Area of application:

-Diesel engines in passenger cars and lorries

-Can be used preventively at every service

-For all diesel fuels, summer and winter diesel

-Suitable for modern common rail and pump nozzle systems

-Can also be used in bio-diesel or mixtures of diesel fuel with bio-diesel

Application: Pour the contents of the container into the tank. Repeat use every 2000 km or if necessary. Fuel volume up to 60 -75 litres of diesel. Minimum fuel capacity according to volume of fuel reserve.

### **Characteristics**

- Cleans diesel system and combustion chambe
- Fuel savings and reduction of CO2 and HC emissions
- Optimum engine performance and smooth engine running
- High corrosion protection
- Increases the lubrication effect for low sulphur fuel
- Improves the ignitability and reduces "rattling sounds" caused by fue

### **Technical Product Data**

PROPERTY	UNIT	DATA	AUDIT
Density at 15 °C	kg/m³	841,2	EN ISO 12185
Colour		light yellow	VISUELL
Pourpoint	°C	-42	DIN ISO 3016
Flashpoint	°C	104	DIN ISO 3679

All indicated data are approximate values and are subject to the commercial fluctuations.