



RAVENOL VFE SAE 5W-20



- 1L | 1111311-001
- 4L | 1111311-004
- 5L | 1111311-005
- 10L | 1111311-010
- 20L | 1111311-020
- 20L | 1111311-B20
- 60L | 1111311-060
- 60L | 1111311-D60
- 208L | 1111311-208
- 208L | 1111311-D28
- 1000L | 1111311-700

Kategorie: Passenger car motor oil

Artikelnummer: 1111311

Viscosity: 5W-20

Specification: API SN Plus, API SP (RC), ILSAC GF-6A

Oil type: Synthetic

Approvals: API SN Plus, API SP Resource Conserving, ILSAC GF-6A

Recommendation: Chrysler MS-6395, Fiat 9.55535-CR1, Ford WSS-M2C925-A, Ford WSS-M2C925-B, Ford WSS-M2C930-A, Ford WSS-M2C930-B, Ford WSS-M2C948-B, Honda/Acura HTO-06, Hyundai, Jaguar Land Rover STJLR.03.5004, KIA, Mazda, Mitsubishi, Nissan, Suzuki, Toyota

Application: Passenger car

Technology: Clean Synto®

RAVENOL VFE SAE 5W-20 is a synthetic, low-friction engine oil with CleanSynto® technology for passenger car gasoline and diesel engines, with and without turbocharging and direct injection.

RAVENOL VFE SAE 5W-20 achieves a high viscosity index through its formulation with special base oils. The excellent cold start behaviour provides an optimum lubricating safety during the cold run phase.

Because of a considerable fuel saving **RAVENOL VFE SAE 5W-20** contributes to protect the environment by reducing the emissions.

RAVENOL VFE SAE 5W-20 minimizes friction, wear and fuel consumption with excellent cold start characteristics.

Suitable for extended oil change intervals where recommended by manufacturer.

Application Note

RAVENOL VFE SAE 5W-20 is an universal fuel-efficient engine oil, a top-quality product for modern passenger cars with gasoline and diesel engines.

Characteristics

- Guaranteed fastest possible lubrication of the engine.
- High fuel economy (FE) effect due to the base oils and additives used.
- Low volatilization tendency, thereby lower oil consumption.
- Provides protection against sludging, coking, varnish and corrosion even under unfavorable operating conditions.
- No oil-related deposits in combustion chambers in the piston ring zone and on valves.
- Ensures the function of the hydraulic tappets at all temperatures.
- Stable engine oil, no NOx oxidation.
- Good soot absorption and dispersion.
- Neutral towards sealing materials.

Technical Product Data

PROPERTY	UNIT	DATA	AUDIT
Density at 20 °C	kg/m ³	853,0	EN ISO 12185
Colour		gelbbraun	VISUELL
Viscosity at 100 °C	mm ² /s	8,2	DIN 51562-1
Viscosity at 40 °C	mm ² /s	47,8	DIN 51562-1
Viscosity Index VI		147	DIN ISO 2909
HTHS Viscosity at 150 °C	mPa*s	2,7	ASTM D5481
CCS Viscosity at -30 °C	mPa*s	6000	ASTM D5293
Low Temp. Pumping viscosity (MRV) at -35 °C	mPa*s	17500	ASTM D4684
Pourpoint	°C	-39	DIN ISO 3016
Noack Volatility	% M/M	9,0	ASTM D5800
Flashpoint	°C	234	DIN EN ISO 2592
tbn	mg KOH/g	7,8	ASTM D2896
Sulphated Ash	%wt.	0,8	DIN 51575

All indicated data are approximate values and are subject to the commercial fluctuations.